

BALLISTIC SPECTACLES

bolle
TACTICAL
bolletactical.ca

RANGER

Certified to STANAG 2920 and EN 172, these ballistic protection sunglasses ensure maximum protection against any event. Thanks to its non-slip bridge, its flexible temples, its lateral ventilation and its design RANGER will provide you comfort and protection. RANGER is available in smoke, polarized and red flash.

INTEGRATED LATERAL PROTECTION
LATERAL VENTILATION

COMFORTABLE AND NON SLIP TEMPLES

BALLISTIC POLYCARBONATE LENS

ANTI-SCRATCH, ANTI-FOG COATINGS

NON-SLIP BRIDGE

NON SLIP BRIDGE

NON-SLIP TEMPLES

ULTRA FLEXIBLE AND COMFORTABLE NYLON FRAME

**HIGH
RESISTANCE**

27 G

Exclusive distributor



Ballistic Resistance STANAG 2920

Smoke lens: v50 188 m/s (677 km/h)
Polarized lens: v50 189 m/s (680 km/h)
Red flash lens: v50 187 m/s (673 km/h)



Options

SUPPLY WITH: MICROFIBER POUCH /
INDIVIDUAL CARRY CASE / INDIVIDUAL
CARTON BOX



RANGER

Safety spectacles

STANDARD MARKINGS :

Products Ref.	LENSES												FRAMES														
	Risks relating to radiations		Bollé Protection Logo	Optical Quality			Mechanical Risks				Electrical Risks	Thermal Risks	Coatings (Optional marking K: anti-scratch N: anti-fog)		CE logo	Bollé Protection logo	Standards	Chemical Risks			Electrical Risks	Mechanical Risks			Thermal Risks	CE logo	
	EN 170 - UV	EN 172 - Solaires (100% UV)		Permanent Wear	Intermittent Wear	Short Period	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	Electric arc short-circuiting	Molten metals and hot solids	anti-scratch	anti-fog				Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short-circuiting	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact		Molten metals and hot solids
RANGPSF		5-3.1		1			F	N/A	N/A	T	N/A						EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	
RANGFLASH		5-3.1		1			F	N/A	N/A	T	N/A						EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	
RANGPOL		5-3.1		1			F	N/A	N/A	T	N/A						EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	

N/A: Non applicable

TACTICAL
Ballistic Resistance
STANAG 2920



Red Flash
V50: 673 km/h (187m/s)



Polarized
V50: 680 km/h (189 m/s)



Smoke
V50: 677 km/h (188m/s)

Notified laboratories for certification :

CHARACTERISTICS :

Lenses	PC - 2,2 mm - Curve 8
Frame	Nylon
Temples	Nylon
Spare Lenses	No

PACKAGING AND EAN13 CODE :

	RANGPSF	RANGFLASH	RANGPOL
individual carry case	3660740001209	3660740001216	3660740001223
N/A	N/A	N/A	N/A
95 safety spectacles per outer pack	3660740201203	3660740201210	3660740201227

